

Burst Plugs

Reliable, Secure
Pressure-Relief System



Features

- Welded one piece assembly - no degradation of joint strength at elevated temperatures
- Inconel rupture disk – stable through a wide range of temperatures
- Burst pressure ranges from 1,000 to 15,000psi
- Accuracy of $\pm 10\%$ of rated burst pressure at 300° – 750°F
- Leak rate exceeds 1×10^{-6} standard cc/sec

Description

The Model BP420 burst plugs are designed specifically for use in plastic extrusion systems. Burst Plugs (also known as rupture disks) are designed for reliable, emergency relief of excess pressure in a system. The Model BP420 will instantaneously rupture at a specific, predetermined pressure and temperature. Each one piece assembly consists of a 304 stainless steel body with a welded Inconel rupture disk. The disk is flush with the tip of the burst plug with no cavity for product build up. A burst plug may be specified for primary relief in applications where pressure build-up can occur so rapidly that the response time of a relief valve is inadequate, such as in a polymerization reaction vessel.

All burst plugs are tested at rated burst pressure and temperature, and each unit is supplied with a burst certificate. In addition, markings on the burst plugs are laser engraved and more visible, and each burst plug is labeled and shipped in a protective package.



www.dynisco.com

Dynisco
38 Forge Parkway
Franklin, MA 02038
USA

Hotline 1-800-Dynisco
www.dynisco.com
Phone +1 508 541 9400
Fax +1-508 541 6206
Email infoinst@dynisco.com

Dynisco Europe, GmbH
Pfaffenstr. 21 Phone +49 7131 297 0
74078 Heilbronn Fax +49 7131 297 166
Germany Email dyniscoeurope@dynisco.com

Dynisco Shanghai
Building #2, ShenFu Road, Phone +86 21 34074072 34074082
Minghang District Toll Free +86 400 728 9117
Shanghai, 201108, P.R.China Fax +86 21 34074025
Email infoinst@dynisco.com

Specifications

MECHANICAL & PACKAGING CHARACTERISTICS

Material of Construction:

Body: 304 stainless steel

Rupture Disk: Inconel

Accuracy: Accuracy of $\pm 10\%$ of rated burst pressure at 300° – 750°F

APPROVALS AND CERTIFICATIONS

ISO: ISO 4126-2:2003(E)


CE: PED 97/23/EC, modules B&D

Burst Certification: Each unit is test burst certified

Mounting Torque: Not to exceed 300 in/lbs.

Ordering Guide

BP420-XXX-XX-XX-XXXX



Shaded sections refer to standard (short lead time) configurations. Contact the factory for other configurations that may be available.

